

# 1080p Mini-Bullet Camera (ADC-VC727P) - Data Sheet

#### Overview

The VC727P is a PoE mini-bullet camera with Two-Way Audio and an adjustable ball joint mount designed for use in indoor and outdoor environments. As part of the commercial Pro Series line, the camera enables intelligent analytics for object detection and business activity tracking. In addition to cloud clip storage, the VC727P supports 24/7 recording to an optional onboard microSD card and/or the Commercial Stream Video Recorder.



## **Key Features**

- 1080p HDR video
- Business Activity Analytics
- Two-Way Audio and Perimeter Guard <sup>™</sup>
- · Onboard Recording with Smart View
- · Video Analytics with Object Detection

- Power over Ethernet
- · IR night vision
- IP66-rated waterproof & dust-tight

## **Included accessories**

- · Mounting hardware
- · Torx wrench
- Weather-resistant RJ-45 cap
- · Drill template

## **Specifications**

Supported resolutions	1920x1080, 1280x720, 640x360		
Local recording	SVR and Onboard Recording  For a list of supported microSD cards and recording resolutions, see Onboard Recording with Smart View.		
Image sensor	1/2.7" progressive scan CMOS		
Field of view	117°		
Low-light sensitivity	0 lux with IR		
IR range	Up to 49 ft (15 m)		
Image adjustments	Flip, brightness, contrast, saturation, sharpness, exposure		
Ethernet connection	10/100 Mbps RJ-45		
Operating temperature	-22°F to 122°F (-30°C to 50°C)		
Operating humidity	20% - 100% non-condensing RH		
Input voltage	12 VDC* ± 10% (5.5mm x 2.1mm barrel connector) or 802.3af type 1 PoE		

Power consumption	Day - IR Off  • 5W  Night - IR On  • 8W  Peak - Heaters On  • 11W
Dimensions	Dimensions (LxWxH): 3.0 x 3.0 x 5.3" (7.5 x 7.5 x 13.4 cm)
Weight	12.5 oz (353 g)
Ingress protection	IP66
Compliance	FCC, IC, RCM, CE Class B, UL, RoHS, WEEE, Compliant with Section 889 of the NDAA**

<sup>\*</sup>Note: When powering Alarm.com devices using a battery bank, the input voltage needs to be regulated with a DC-DC converter. If you are not sure how to set up that configuration, contact a certified electrician.

## **Business Activity Analytics**

### Occupancy & people counting

Measure occupancy and foot traffic. Receive a notification when real-time occupancy reaches a specified threshold.

#### **People counting**

Measure foot traffic through a certain area. Count how many people cross a virtual line in one direction.

#### **Queue monitoring**

Monitor people waiting in line. Receive a notification when the number of people in line or average wait time reaches a specified threshold.

<sup>\*\*</sup>Note: Accurate as of 9/23/24. Visit Alarm.com > Legal > NDAA Statement for the most current information.

#### **Crowd gathering**

Monitor large groups. Receive a notification when the crowd size reaches a specified threshold.

## **Heat mapping**

Visualize where people spend the most time within an area during a specified date and time range using a heat map.

For more information about Business Activity Analytics, see Business Activity Analytics (BAA) Setup.

## Onboard Recording with Smart View

Record encrypted, 24/7 HD footage locally on the camera with a microSD card. View live and recorded video on the Alarm.com Customer website and Customer app from anywhere, using the Smart View video timeline to search for important events such as person detected or door accessed, and jump straight to the corresponding footage.

For more information about Onboard Recording, see Onboard Recording with Smart View for video devices.

#### Approximate days of recording

Recording Quality	32GB	64GB	128GB	256GB	512GE
1920x1080 30FPS	1 Day	2 Days	5 Days	10 Days	20 day
1920x1080 15FPS	2 Days	4 Days	7 Days	15 Days	30 day
1280x720 10FPS	4 Days	7 Days	15 Days	29 Days	60 day
640x480 10FPS	7 Days	15 Days	29 Days	59 Days	119 da

## Two-Way Audio & Perimeter Guard<sup>™</sup>

Safely speak with delivery personnel, guests, or unwanted visitors from anywhere using the camera's powerful speaker and microphone. Plus, Perimeter Guard<sup>™</sup> can proactively deter intruders with its attention-grabbing audio and flashing red LED alerts when someone is detected after hours.

For more information about Two-Way Audio, see Two-Way Audio Installation and User Guide.

For more information about Perimeter Guard, see Perimeter Guard for video devices.